

Supplier's name or trade mark:	MEGAMAN GmbH
Supplier's address	Halskestraße 22-26, AircomParc A140880 RatingenGermany

Model identifier	SDS731v0dm828
Equivalent Models	N/A

Technical Document

Useful luminous flux	470
On-mode Power (Pon)	4.1 W
Beam angle in degrees for directional light sources (DLS)	100
Peak luminous intensity in cd for directional light sources (DLS)	210
Correlated Colour Temperature	2800 K
Chromaticity coordinates (x,y)	0.463, 0.413
Colour Rendering Index (CRI)	Ra 80
Standby Power (Psb)	N/A
Networked Standby Power (Pnet)	N/A
R9 colour rendering index value for LED and OLED light sources	0
Survival factor for LED and OLED light sources	0.90
Lumen maintenance factor for LED and OLED light sources	0.958
Indicative lifetime L70B50 for LED and OLED light sources	25000
Displacement Factor (cos φ1)	0.9
Colour Consistency	SDCM ≤ 6
Luminance for HLLS	N/A
Flicker metric (PstLM)	1
Stroboscopic effect metric (SVM)	0.4
Excitation purity for CTLS	N/A
Weighted Energy Consumption	5 kWh/1000hrs
Energy Efficiency Class	E
Outer dimensions in mm	
Height	51
Width	83
Depth	83
Standards Compliance	CE, RoHS

CALCULATIONS - GENERAL RULE

Refer to Annex II of Energy Labelling (EU) 2019/2015

Energy efficiency classes and calculation method

The energy efficiency class of light sources shall be determined as set out in Table 1, on the basis of the total mains efficacy η_{TM} , which is calculated by dividing the declared useful luminous flux Φ_{use} (expressed in *lm*) by the declared on-mode power consumption P_{on} (expressed in *W*) and multiplying by the applicable factor FTM of Table 2, as follows:

$$\eta_{TM} = (\Phi_{use}/P_{on}) \times FTM \text{ (lm/W)}$$

Table 1

Energy efficiency classes of light sources

Energy efficiency class	Total mains efficacy η_{TM} (lm/W)
A	$210 \leq \eta_{TM}$
B	$185 \leq \eta_{TM} < 210$
C	$160 \leq \eta_{TM} < 185$
D	$135 \leq \eta_{TM} < 160$
E	$110 \leq \eta_{TM} < 135$
F	$85 \leq \eta_{TM} < 110$
G	$\eta_{TM} < 85$

Table 2

Factors FTM by light source type

Light source type	Factor FTM
-------------------	------------

Non-directional (NDLS) operating on mains (MLS)	1,000
Non-directional (NDLS) not operating on mains (NMLS)	0,926
Directional (DLS) operating on mains (MLS)	1,176
Directional (DLS) not operating on mains (NMLS)	1,089

ADDITIONAL PART

A list of compatible dimmers shall be provided on the website www.megaman.cc

MEGAMAN | WEEE - Green Room | LED, Energy-efficient & Eco-friendly Lighting, Restriction of Hazardous Substances

<https://www.megaman.cc/resources/green-room/weee>

MEGAMAN GmbH
Halskestraße 22-26, AircomParc A1
40880 Ratingen
Germany



Model no.: FDS73100v0-dm

Light source model identifier: SDS731v0dm828, SDS731v0dm840

Light source: Removable

SDS731v0dm828/ SDS731v0dm840 I in: 930mA U in 45VDC

<p>WHOLE LIGHT</p> 	<p>Step1: TAKE OUT THE LIGHT SOURCE FORM THE FIXTUEER</p>  	<p>Step2: DIVIDE THE RING</p>  
<p>Step3: TAKE OUT THE DIFFUSER</p>  	<p>Step4 : UNSCREW THE FOUR SCREW</p>  	<p>Step5: CUT OFF THE WIRE</p>  <p>STEP 6 LIGHT SHOURCE</p> 