

Supplier's name or trade mark:	MEGAMAN GmbH
Supplier's address	Halskestraße 22-26, AircomParc A140880 RatingenGermany

Model identifier	SOB776v0da840
Equivalent Models	N/A

Technical Document

Useful luminous flux	6890
On-mode Power (Pon)	44 W
Beam angle in degrees for directional light sources (DLS)	N/A
Peak luminous intensity in cd for directional light sources (DLS)	N/A
Correlated Colour Temperature	4000 K
Chromaticity coordinates (x,y)	0.382, 0.382
Colour Rendering Index (CRI)	Ra 80
Standby Power (Psb)	N/A
Networked Standby Power (Pnet)	N/A
R9 colour rendering index value for LED and OLED light sources	0
Survival factor for LED and OLED light sources	0.90
Lumen maintenance factor for LED and OLED light sources	0.98
Indicative lifetime L70B50 for LED and OLED light sources	50000
Displacement Factor (cos φ1)	0.9
Colour Consistency	SDCM ≤ 6
Luminance for HLLS	N/A
Flicker metric (PstLM)	0.8
Stroboscopic effect metric (SVM)	0.4
Excitation purity for CTLS	N/A
Weighted Energy Consumption	44 kWh/1000hrs
Energy Efficiency Class	D
Outer dimensions in mm	
Height	4
Width	27
Depth	1314
Standards Compliance	CE, RoHS

CALCULATIONS - GENERAL RULE

Refer to Annex II of Energy Labelling (EU) 2019/2015

Energy efficiency classes and calculation method

The energy efficiency class of light sources shall be determined as set out in Table 1, on the basis of the total mains efficacy η_{TM} , which is calculated by dividing the declared useful luminous flux Φ_{use} (expressed in lm) by the declared on-mode power consumption P_{on} (expressed in W) and multiplying by the applicable factor FTM of Table 2, as follows:

$$\eta_{TM} = (\Phi_{use}/P_{on}) \times FTM \text{ (lm/W)}$$

Table 1

Energy efficiency classes of light sources

Energy efficiency class	Total mains efficacy η_{TM} (lm/W)
A	$210 \leq \eta_{TM}$
B	$185 \leq \eta_{TM} < 210$
C	$160 \leq \eta_{TM} < 185$
D	$135 \leq \eta_{TM} < 160$
E	$110 \leq \eta_{TM} < 135$
F	$85 \leq \eta_{TM} < 110$
G	$\eta_{TM} < 85$

Table 2

Factors FTM by light source type

Light source type	Factor FTM
-------------------	------------

Non-directional (NDLS) operating on mains (MLS)	1,000
Non-directional (NDLS) not operating on mains (NMLS)	0,926
Directional (DLS) operating on mains (MLS)	1,176
Directional (DLS) not operating on mains (NMLS)	1,089

ADDITIONAL PART

A list of compatible dimmers shall be provided on the website www.megaman.cc

MEGAMAN | WEEE - Green Room | LED, Energy-efficient & Eco-friendly Lighting, Restriction of Hazardous Substances

<https://www.megaman.cc/resources/green-room/weee>

MEGAMAN GmbH
Halskestraße 22-26, AircomParc A1
40880 Ratingen
Germany



Removable Light Source

Model No.	Light source Model identifier	Input Voltage (VDC)	Input Current (mA)
FOB77400v0	SOB774v0840	DC 400	38
FOB77500v0-ds	SOB775v0840	DC 400	75
FOB77600v0-ds	SOB776v0840	DC 400	115
FOB77400v1	SOB774v1840	DC 400	38
FOB77500v1-ds	SOB775v1840	DC 400	75
FOB77600v1-ds	SOB776v1840	DC 400	115
FOB77600v3-ds	SOB776v3840	DC 109	585

