

MEGAMAN® RENZO



MEGAMAN® RENZO is an energy efficient integrated surface mounted LED luminaire with a wide range of lumen packages for a perfect alternative to traditional wall-mounted compact fluorescent luminaires (alternative for 1x18W up to 2x26W CFL). It comes with an opal PMMA diffuser that delivers evenly distributed lighting and visual comfort.

A built-in microwave motion sensor option is available. MEGAMAN® RENZO with microwave motion sensor turns the light on when entering and leaving the room.

Features


- Energy efficient replacement for interior CFL luminaires
- A wide range of lumen packages for a perfect alternative to traditional wall and ceiling mounted luminaires (replacing CFL from 1x18W up to 2x26W)
- IP44 version available for high moisture locations
- The built-in microwave motion sensor option uses low power microwave signals which are reflected by moving person, perfect for stairwell and walkway application
- Suitable for surface mounting on solid walls or ceilings
- Unobtrusive and understated design style for all situations
- Opal PMMA diffuser for an evenly distributed light effect and visual comfort

Applications


- Hotels
- Bathrooms
- Kitchens
- Corridors
- Residential applications

MEGAMAN® RENZO


F50500SM / F50500SM+IP44



F50600SM / F50600SM+IP44



F50600SM-r+IP44




White (WH26)


Model No.	Voltage (V)	Wattage (W)	Luminous Flux (lm)	Luminous Efficacy (lm/W)	Dimension (mm)	IP Rating	Colour Temp. [CRI]	Rated Life (hrs)	Housing Materials	Diffuser Materials	Weight (g)
NEW F50500SM	220-240	10.5	800	76	Ø280 x H85	IP20	3000K / 4000K [>Ra80]	25000	Steel	PMMA	374
NEW F50500SM+IP44	220-240	10.5	800	76	Ø280 x H85	IP44	3000K / 4000K [>Ra80]	25000	Steel	PMMA	400
NEW F50600SM	220-240	14.5	1100	76	Ø340 x H105	IP20	3000K / 4000K [>Ra80]	25000	Steel	PMMA	560
NEW F50600SM+IP44	220-240	14.5	1100	76	Ø340 x H105	IP44	3000K / 4000K [>Ra80]	25000	Steel	PMMA	604
NEW F50600SM-r+IP44	220-240	15.5	1100	71	Ø340 x H105	IP44	3000K / 4000K [>Ra80]	25000	Steel	PMMA	652

With microwave motion sensor

F50500SM / F50500SM+IP44




F50600SM / F50600SM+IP44 / F50600SM-r+IP44




MEGAMAN® RENZO


F50700SM / F50700SM+IP44





F50700SM-r+IP44



White (WH26)

Model No.	Voltage (V)	Wattage (W)	Luminous Flux (lm)	Luminous Efficacy (lm/W)	Dimension (mm)	IP Rating	Colour Temp. [CRI]	Rated Life (hrs)	Housing Materials	Diffuser Materials	Weight (g)
NEW F50700SM	220-240	18.5	1400	76	Ø390 x H110	IP20	3000K / 4000K [>Ra80]	25000	Steel	PMMA	700
NEW F50700SM+IP44	220-240	18.5	1400	76	Ø390 x H110	IP44	3000K / 4000K [>Ra80]	25000	Steel	PMMA	740
NEW F50700SM-r+IP44 	220-240	19.5	1400	72	Ø390 x H110	IP44	3000K / 4000K [>Ra80]	25000	Steel	PMMA	788

 With microwave motion sensor





5 FT

4 FT

4 FT

