

MEGAMAN® TOTT



MEGAMAN® TOTT works perfectly with the double-ended LED R7s to replace halogen outdoor floodlights while offering up to 25,000 hours lamp life, MEGAMAN® TOTT is also available as an integrated LED with built-in driver, and in different sizes for high lumen output applications. MEGAMAN® TOTT is made of durable aluminium material but has a compact profile and is extra light in weight; it offers powerful and uniform floodlight illumination.

Designed for outdoor directional floodlighting, MEGAMAN® TOTT has rust-free finish and up to IP65 protection, with a flexible tilt angle.


Features

- Working with double-ended LED R7s, MEGAMAN® TOTT is a halogen replacement that offers up to 25,000 hours lamp life
- LED chip-on-board with integrated driver version available for high lumen output applications
- Up to IP65 protection, perfect for outdoor use
- Flexible tilt angle for directional floodlighting
- Offers powerful and uniform floodlight illumination in compact profile
- Different sizes (small, medium, and large) for different applications
- PIR sensor version available for energy savings
- Made with extra light weight and durable aluminium material
- Rust-free finish

Applications



- Signages
- Billboards
- Gate areas
- Pillar facades

F25500SM+IP54 / F25500SM+IP65




TOTT S

F25400SM+IP54 / F25400SM+IP65




TOTT M

F25600SM+IP54 / F25600SM+IP65




TOTT L




Model No.	Voltage (V)	Wattage (W)	Luminous Flux (lm)	Luminous Efficacy (lm/W)	Dimension (mm)	Max. Luminous Intensity (cd) [Beam Angle]	IP Rating	Colour Temp. [CRI]	Rated Life (hrs)	Materials	Weight (g)
F25500SM+IP54	220-240	12	900	75	W86 x L114 x H104	600 [80°]	IP54	3000K / 4000K [Ra80]	25000	Aluminium	370
F25500SM+IP65	220-240	12	900	75	W86 x L114 x H104	600 [80°]	IP65	3000K / 4000K [Ra80]	25000	Aluminium	551
F25400SM+IP54	220-240	33	2300	70	W141 x L181 x H129	1065 [100°]	IP54	3000K / 4000K [Ra80]	25000	Aluminium	1049
F25400SM+IP65	220-240	33	2300	70	W141 x L181 x H129	1065 [100°]	IP65	3000K / 4000K [Ra80]	25000	Aluminium	1210
F25600SM+IP54	220-240	60	4200	70	W238 x L287 x H172	2000 [100°]	IP54	3000K / 4000K [Ra80]	25000	Aluminium	2728
F25600SM+IP65	220-240	60	4200	70	W238 x L287 x H172	2000 [100°]	IP65	3000K / 4000K [Ra80]	25000	Aluminium	2909


F25500SM+IP54 / F25500SM+IP65



F25400SM+IP54 / F25400SM+IP65



F25600SM+IP54 / F25600SM+IP65





MEGAMAN® TOTT

F25546SM





TOTT S



F25447SM



TOTT M



Model No.	Max. Wattage (W)	Dimension (mm)	Light Source	Lamp Base	Materials	Weight (g)
F25546SM	7	W96 x L138 x H178	LED R7s	R7s	Aluminium Alloy	505
F25447SM	9	W125 x L185 x H260	LED R7s	R7s	Aluminium Alloy	990

